AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior version and listings of claims in the application:

Listing of Claims:

- 1. (Previously presented): A method of time charging to DHCP online users in a broadband access server, comprising the steps of:
 - setting an inner time, an outer time and a flow threshold for counting data flow of the users in the broadband access server, the inner time being shorter than the outer time;
 - b) starting time charging to the users by instruction of the access server to the users sooner after the users access the access server and are authenticated successfully,
 - c) establishing a circular link list to each user for recording data flow of the user in the access server;
 - d) defining a number of elements in the circular link list as a multiple of the outer time to the inner time in the access server; and
 - e) detecting the data flow of the user according to the inner time in the access server, and recording the data flow as a content of a head pointer of the circular link list in turn, until a difference between data flow newly detected and the content rerecorded in the head pointer is not more than the flow threshold.
- 2. (Previously presented): The method of claim 1, characterized in that, when the circular link list is not full, step e) further comprises the step of:
 - e1) examining data flow newly detected and the content of the head pointer, when a difference between data flow newly detected and the content of the head pointer exceeds the flow threshold, saving the data flow newly detected as the content of the head pointer, and, meanwhile, moving the head and tail pointers down a position.

2

- 3. (Previously presented): The method as claimed in claim 1, characterized in that, when the circular link list is full, step e) further comprises the step of:
 - e2) examining data flow newly detected and the content of the head pointer element, when a difference between data flow newly detected and the content of the head pointer exceeds the flow threshold, saving the data flow newly detected as the content of the head pointer, and moving the head and tail pointers down a position.
- 4. (Previously presented): The method of claim 2, characterized in that the method further comprises the steps of:
 - f) deciding the user in an IDLE state in the access server when the difference between the data flow newly detected and the content recorded in the head pointer does not exceed the flow threshold; and
 - g) stopping time charging to the user by instruction of the access server to the user.
- 5. (Original): The method of claim 4, characterized in that the method further comprises the step of setting the user in an unauthenticated state in step f).
- 6. (Previously presented): The method of claim 4, characterized in that the method further comprises the step of setting a charging server for time charging to the online users in step b).
- 7. (Original): The method of claim 6, characterized in that the time for the charging server to stop time charging is before an outer time corresponding to the inner time when the IDLE state is detected.
- 8. (Original): The method of claim 5, characterized in that the inner time is about 30 seconds and/or the outer time is about 5 minutes.

9. (Currently amended): A method of time charging to DHCP online users in a broadband access server, characterized in that the method comprises the steps of:

setting an inner time interval, an outer time interval and a flow threshold in the broadband access server, the inner time interval being shorter than the outer time interval;

detecting data flow of an authenticated user by using [[an]]the inner time interval being shorter than [[an]]the outer time interval and [[a]]the flow threshold in the broadband access server and establishing a circular link list corresponding the user so as to decide whether the user is in an IDLE state; and

if the user is not in the IDLE state, recording current data flow in the circular link list and continuedly detecting the data flow; otherwise, determining the user in IDLE state.

10. (Original): The method of claim 9, characterized in that the method further comprises the steps of:

assigning an IP address through the broadband access server to a user and authenticating the user;

starting time charging to the user from the time when the user is authenticated successfully;

calculating a number of elements in a circular link list according to the inner time and the outer time configured;

updating the information of the user flow timely; detecting an IDLE state of the user; and forcing the user in IDLE state to log out.

- 11. (Previously presented): The method of claim 3, characterized in that the method further comprises the steps of:
 - f) deciding the user in an IDLE state in the access server when the difference between the data flow newly detected and the content recorded in the head pointer does not exceed the flow threshold; and

Appl. No. 10/563,496 Response Dated April 8, 2009 Reply to Office Communication of March 16, 2009

- g) stopping time charging to the user by instruction of the access server.
- 12. (Previously presented): The method of claim 5, characterized in that the method further comprises the step of setting a charging server for time charging to online users in step b).